Development of light guides for the camera of CANGAROO-III telescope

F. Kajino¹, J. Patterson¹, S. Dazeley¹, D. Swaby², S. Yanagita², T. Yoshida², C. Ito³, T. Kifune³, M. Mori³, R. Enomoto³, A. Kawachi³, K. Okumura⁴, R. Suzuki⁴, H. Katagiri⁴, K. Tsuchiya⁴, M. Ohishi⁴, S. Kabuki⁴, H. Tsunoo⁴, R. Susukita⁵, P. G. Edwards⁶, T. Tamura⁷, Y. Mizumoto⁸, K. Nishijima⁸, T. Nakase⁸, K. Uruma⁹, A. Asahara⁹, S. Hara⁹, M. Moriya⁹, K. Sakurazawa¹⁰, K. Takano¹⁰, J. Kushida¹⁰, S. Ogio¹⁰, T. Tanimori¹⁰, H. Kubo¹⁰, J. Kataoka¹⁰, R. Orito¹¹, Y. Muraki¹¹, Y. Matsubara¹¹, A. Yuki¹², S. Gunji¹², F. Tokanai¹², F. Takano¹², A. Watanabe¹³, T. Hara¹³, T. Naito¹⁴, T. Yoshikoshi¹⁵, S. Hayashi¹⁵, A. Maeshiro¹⁵, S. Maeda¹⁶, H. Muraishi¹⁷, and G. Bicknell¹⁸

¹Konan University, Okamoto, Kobe 658-8501, Japan

Abstract. The camera of the CANGAROO-III Cherenkov Telescope is consists of many photomultiplier tubes (PMTs), with significant dead space between the PMTs. Light guides re ect photons directed at dead spaces to the effective area of a PMT. We performed Monte Carlo simulations for various shapes of light guides to evaluate their performance, compared with experimental values, and deter-mined the optimal shape of the light guide for the CANGAROO-III Telescope.

The best collection efficiency was obtained for the following conditions: The cross sectional shape cut along the center line of the light guide should have the Winston cone shape, though the entrance shape is hexagonal, and the gap between the light guide and the PMT should be as small as possible. To de-crease the detectable energy threshold, good light collection efficiency is very important.

²The University of Adelaide

³Ibaraki University

⁴ICRR, The University of Tokyo

⁵Riken

⁶ISAS

⁷Kanagawa University

⁸NAOJ

⁹Tokai University

¹⁰Tokyo Inst. Tech.

¹¹Kyoto University

¹²STE Lab, Nagoya University

¹³Yamagata University,

¹⁴Yamanashi Gakuin University

¹⁵Osaka City University

¹⁶Konan University

¹⁷Ibaraki Pref. University of Health Sci.

¹⁸MSSSO, Australian National University